

KRPA-11AG-240

✓ ACTIVE

Potter & Brumfield | Potter & Brumfield KRPA

TE Internal #: 2-1393104-7

General Purpose Power Relay, AC, Monostable, 2 Form C DPDT-CO, 10 A Contact Rating, 240 VAC Coil Voltage, Potter & Brumfield KRPA

[View on TE.com >](#)



Relays & Contactors > Electromechanical Relays



Relay & Contactor Type: **General Purpose Power Relay**

Current Type: **AC**

Coil Magnetic System: **Monostable**

Contact Arrangement: **2 Form C DPDT-CO**

Contact Current Rating: **10 A**

Features

Product Type Features

Relay & Contactor Type	General Purpose Power Relay
------------------------	-----------------------------

Configuration Features

Contact Number of Poles	2
Coil Special Features	UL Coil Insulation Class B
Contact Arrangement	2 Form C DPDT-CO

Electrical Characteristics

Contact Limiting Short-Time Current	10 A
Contact Limiting Making Current	10 A
Contact Limiting Continuous Current	10 A
Contact Limiting Breaking Current	10 A
Insulation Initial Dielectric Between Open Contacts	1000 Vrms
Insulation Initial Dielectric Between Adjacent Contacts	1000 Vrms
Contact Switching Load (Min)	300mA @ 12V
Coil Resistance	9110 Ω
Coil Power Rating AC	2.1 VA
Insulation Initial Resistance	1000 MΩ
Contact Current Rating	10 A
Coil Voltage Rating	240 VAC



Contact Voltage Rating	240 VAC
Insulation Initial Dielectric Between Contacts & Coil	1000 Vrms

Body Features

Product Weight	85 g[2.988 oz]
Enclosure Type	Dust Protected

Contact Features

Contact Material	Silver Cadmium Oxide
------------------	----------------------

Termination Features

Main Termination & Connection Type	Socket Pins
Coil Termination & Connection Type	Socket Pins

Mechanical Attachment

Product Mounting Feature Type	Mounting Studs
Product Mount Type	Panel & Socket Mount

Dimensions

Product Width	35.71 mm[1.4 in]
Product Length	35.71 mm[1.4 in]
Product Height	50.8 mm[2 in]

Usage Conditions

Operating Temperature Range	-45 – 55 °C[-49 – 131 °F]
Environmental Category of Protection	RTI
Environmental Ambient Temperature (Max)	55 °C[131 °F]

Operation/Application

Current Type	AC
Coil Magnetic System	Monostable

Packaging Features

Packaging Method	Tray
------------------	------

Other

Contact Current Class	>5 – ≤10 A
Height Class (Mechanical)	50 – 60 mm
Length Class (Mechanical)	35 – 40 mm
Width Class (Mechanical)	30 – 40 mm



Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Not Yet Reviewed
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) SVHC > Threshold: Cd (7.5% in Component Part) Cadmium oxide (4.37% in 4735210816) Article Safe Usage Statements: Use personal protective equipment as required. Do not eat, drink or smoke when using this product. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



TE Part # 1393143-7
27E123=SOCKET,KRP,11,SCW,SURF-MOUNT



TE Part # 2-1419106-4
27E892=SOCKET,KRPA,11,OCTAL,DINRAIL

Also in the Series | [Potter & Brumfield KRPA](#)

A collection of various AC relays, including a large white one with multiple terminals and several smaller black and silver ones.

AC Relays(21)

A collection of various DC relays, including a large silver one with multiple terminals and several smaller black and silver ones.

DC Relays(24)

A collection of various electromechanical relays, including a large black one with multiple terminals and several smaller black and silver ones.

Electromechanical Relays(45)

A collection of various plug-in relays, including a large black one with multiple terminals and several smaller black and silver ones.

Plug-In Relays(45)

A collection of various relay accessories, including a large white one with multiple terminals and several smaller black and silver ones.

Relay Accessories(4)

Customers Also Bought

A black metal terminal with a ring and a threaded end.

TE Part #31805
TERMINAL,SOLIS R 12-10 10

A black metal terminal with a ring and a threaded end.

TE Part #2-321684-1
TERMINAL,SOLIS R 16-14 6

A yellow cylindrical terminal with a ring and a threaded end.

TE Part #324915
TERMINAL,PIDG R 12-10 8

A black metal terminal with a ring and a threaded end.

TE Part #2-1393104-5
KRPA-11AG-120=KRPA-

A black metal terminal with a ring and a threaded end.

TE Part #6-1393104-5
KRPA-14AG-120=KRPA

A black metal terminal with a ring and a threaded end.

TE Part #8-1393104-5
KRPA-14DG-48=KRPA

A black metal terminal with a ring and a threaded end.

TE Part #8-1393113-3
KUEP-11A15-120=RELAY,GENPUR,QC

A black metal terminal with a ring and a threaded end.

TE Part #8-1393113-6
KUEP-11D15-12=KU

A black metal terminal with a ring and a threaded end.

TE Part #9-1393113-7
KUEP-3D15-110=KU

A black metal terminal with a ring and a threaded end.

TE Part #4-1393117-3
KUP-11D15-110=KU

Documents



CAD Files

Customer View Model

ENG_CVM_CVM_2-1393104-7_D.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2-1393104-7_D.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2-1393104-7_D.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

KRPA, KRP, KA, KR 5 to 10 Amp General Purpose Relay

English

KR Sockets & Accessories

English

Product Specifications

Definitions General Purpose Relays

English

Agency Approvals

UL

English