



Fuse-link, high speed, 315 A, AC 240 V, 200 kA, BS88, 39 x 84 mm, aR, BS, Sealed, 57 mm fixing centres

Part no. **SEALED FUSE 315A 240V**
Catalog No. **315SBMT**

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			high speed
Rated current	I	A	315
Rated voltage			AC 240 V
Construction size			BS88
Size			39 x 84 mm
Utilization category			aR
Description			Sealed 57 mm fixing centres
Breaking Capacity		kA	200
usable for size/applications			for rotating rectifiers
Standard/Approval			BS
Shape			centre-bolted tags
Standards/Regulations			BS88-4 IEC 60269-4

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 (AFZ800015))			
Construction size			Other
Rated current		A	315
Rated voltage		V	240
Voltage type			AC
Rated switching capacity		kA	200
Utilization category			aR (accompanied semiconductor protection)
Type of fuse status indicator			None
Insulated metal gripping lugs (IMGL)			No

Additional product information (links)

Product datasheet (pdf)	http://www1.cooperbusssmann.com/pdf/4a317260-8e98-40d9-b43b-e80c53a102f6.pdf
-------------------------	---