



Part no.
Article no.

BUSS MIDGET FUSE FAST ACTING
BBS-1

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			low voltage
Rated current	I	A	1
Rated voltage			AC 600 V
Size			10.3 x 34.9 mm
Utilization category			supplemental
usable for size/applications			control and electronic circuits, hand-held meters, HID ballasts
Release characteristic	class		fast-acting
Standard/Approval			UL CSA
Shape			cylindrical
Material			fiber body
Standards/Regulations			UL 248-14

Technical data ETIM 6.0

Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Cylindrical fuse (safety fuse) (ecI@ss8.1-27-14-20-02 [AFZ797010])			
Size			Other
Rated voltage			AC 600 V
Nominal current		A	1
With striker			No

Additional product information (links)

Product datasheet (pdf)	http://www.cooperindustries.com/content/dam/public/bussmann/Electrical/Resources/product-datasheets-a/Bus_Ele_DS_2010_BBS.pdf
Product datasheet (web)	http://www.cooperindustries.com/content/public/en/bussmann/electrical/products/supplemental/fast_acting_midget/bbs.html