



Fuse-link, high speed, 16 A, AC 690 V, 200 kA, DIN 000, gR, DIN, IEC, type T indicator, live gripping lugs



Part no. FUSE 16A 690V gR DIN 000 HSDNH
Catalog No. 170M1559D

Similar to illustration

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			high speed
Rated current	I	A	16
Rated voltage			AC 690 V
Construction size			DIN 000
Utilization category			gR
Status indicator			type T indicator
Description			live gripping lugs
Breaking Capacity		kA	200
usable for size/applications			semiconductor protection
Standard/Approval			DIN IEC
Shape			square body with knife blade contacts
Standards/Regulations			DIN 43620 IEC 60269-4
Optional accessories			microswitches 170H0238, 170H0236

Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss10.0.1-27-14-20-90 [BAB264011])			
Fuse construction type according to IEC 60269			Other
Type of current			
Rated voltage AC		V	690
Rated voltage DC		V	
Rated current		A	16
Utilization category			gR (general purpose semiconductor protection)
Breaking capacity		kA	
Colour code			
Type of fuse status indicator			Combination fuse status indicator
Power loss at rated current		W	4
Mounting holes			
Centre-to-centre distance of connections		mm	