



**House service fuse-link, low voltage, 60 A, AC 415 V, 33 kA, BS system C type II, 23 x 57 mm, gL/gG, BS**

**Part no. 60A 415V AC HOUSE SERVICE**  
**Catalog No. 60KR85**

## Delivery program

|                              |   |    |                                                                          |
|------------------------------|---|----|--------------------------------------------------------------------------|
| Product range                |   |    | Fuse                                                                     |
| Basic function               |   |    | House service fuse-link                                                  |
| Field of application         |   |    | low voltage                                                              |
| Rated current                | I | A  | 60                                                                       |
| Rated voltage                |   |    | AC 415 V                                                                 |
| Construction size            |   |    | BS system C type II                                                      |
| Size                         |   |    | 23 x 57 mm                                                               |
| Utilization category         |   |    | gL/gG                                                                    |
| Breaking Capacity            |   | kA | 33                                                                       |
| usable for size/applications |   |    | protection of incoming cables into residential and commercial properties |
| Standard/Approval            |   |    | BS                                                                       |
| Shape                        |   |    | cylindrical                                                              |
| Standards/Regulations        |   |    | BS88-3                                                                   |
| Optional accessories         |   |    | house-service cut-out 6080SP                                             |

## Technical data ETIM 7.0

|                                                                                                                                                                                               |  |    |                                               |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|----|-----------------------------------------------|
| Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704)                                                                                                                           |  |    |                                               |
| Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Cylindrical fuse (safety fuse) (ecl@ss10.0.1-27-14-20-02 [AFZ797013]) |  |    |                                               |
| Size                                                                                                                                                                                          |  |    | Other                                         |
| Rated voltage                                                                                                                                                                                 |  | V  | 415 - 415                                     |
| Rated voltage                                                                                                                                                                                 |  |    | Other                                         |
| Voltage type                                                                                                                                                                                  |  |    | AC                                            |
| Utilization category                                                                                                                                                                          |  |    | gL/gG (cable protection/equipment protection) |
| Rated operating frequency                                                                                                                                                                     |  | Hz | 45 - 62                                       |
| Nominal current                                                                                                                                                                               |  | A  | 60                                            |
| With striker                                                                                                                                                                                  |  |    | No                                            |
| Release characteristic                                                                                                                                                                        |  |    | Other                                         |
| Breaking capacity                                                                                                                                                                             |  | kA | 33                                            |